

130 liter tank i Syrafast 316



96 000 SEK /st exkl moms

Additional information: Handhole DN 250; 1 vessel (manufactured in 2012) made of material 1.4435 (stainless steel 316); slight variations from the other two vessels are possible; Includes complete documentation from a GMP-certified pharmaceutical manufacturing facility

Volumetric volume (L): 130 L



Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Outlet of tank: 25

Cylinder: 6 mm

Internal diameter tank: 550 mm

Outer diameter tank: 700 mm

Cylinder height: 354 mm

Total height of tank: 1.380 mm

SKU: 704788



Mer information

Beskrivning av produkt

Material: Syrefast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Brukt

Arbetstryck i tank: vakuum

Konfiguration: isolert

Max. arbetstemperatur: 150 °C

Mobil tank: Nei, det er det ikke.

Övrig information: Handhole DN 250; 1 vessel (manufactured in 2012) made of material 1.4435 (stainless steel 316); slight variations from the other two vessels are possible; Includes complete documentation from a

Övrig information2: GMP-certified pharmaceutical manufacturing facility

Omrörare: Nei

Total urtappning: Ja

Undertryck (vakuum): 1 bar

Uppvärmning/kylning: Nei, det er det ikke.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 130

Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nei, det er det ikke.

Översikt material

Material: Syrefast 316

Dimensioner av tank

Cylinderhöjd: 354 mm

Invändig diameter: 550 mm

Total höjd: 1380 mm

Ytterdiameter: 700 mm



Tjocklek på tank

Cylinder: 6 millimeter

Mer

Isolerad: Ja