1300 liter tank i Rostfritt 304



87 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank
Volumetric volume (L): 1.300 L
Pressure in tank: pressure
Max. pressure (Bar): 2 Bar
Min. pressure (Bar): -0,15 Bar

Max. temperature (°C): 130 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes
Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: strong conical
Bottom outlet: yes
Total discharge: yes
Fixation points: 4 non adjustable feet
Type of HE on the cylinder: dimple-jacket

Position HE: the complet cilinder
Water pressure HE: 5,20 Bar
Working temperature HE cylinder: 80 °C
Type of HE on the bottom: dimple-jacket
Heat exchanger bottom connected with cylinder: yes

Water pressure HE: 5,20 Bar
Working temperature HE bottom: 80 °C
Heat exchanger: RVS 304
Manway(s): RVS 304
Gasket manway(s): EPDM

Valve: RVS 304L
Gasket shut-off valve (mat): EPDM
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: headside

CIP spray ball: no, optional
Tank outlet: inside Ø 32 mm

Outlet type: DN32
Total outlet valve: yes
Agitator: no, optional

Top: 2 mm
Cylinder: 2 mm
Bottom: 3 mm
Distance from outlet to ground: 326 mm
Outer diameter tank: 1.140 mm

Cylinder height: 935 mm
Total height of tank: 2.018 mm
Empty weight tank: 179

SKU: 450488

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 130 °C
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Omrörare: Nej
Övertryck: 2 Bar
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: strong conical
Undertryck (vakuum): -0,15 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1300

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 32 mm
Teknisk ritning finns: Ja
Utloppstyp: DN32
Utloppsventil: Ja

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 935 mm
Mått utlopp till marken: 326 mm
Total höjd: 2.018 mm
Ytterdiameter: 1.140 mm

Värmeväxlare

Arbetstemperatur värmeväxlare cylinder: 80 °C
Arbetstemperatur värmeväxlare botten: 80 °C
Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Typ av värmeväxlare på botten: dimple-jacket
Vattentryck värmeväxlare: 5,20 Bar
Vattentryck värmeväxlare botten: 5,20 Bar

Tjocklek på tank

Botten: 3 mm
Cylinder: 2 mm
Topp: 2 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 179