1300 liter tank i Syrafast 316



133 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; 1 vessel is missing the agitator; 1 vessel with insulation; 2 stainless steel 304 claws (contact surface the other way round; flanges partly made of Fe (see photos); some residues of previous content
Volumetric volume (L): 1.300 L
Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 23 L
Max Overpressure: 16 Bar

Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN80
Agitator: yes
Number of revolutions: 571

Power: 1,10
Top: 4,10 mm
Cylinder: 5 mm
Bottom: 3 mm
Internal diameter tank: 990 mm

Cylinder height: 1.330 mm

SKU: 397967

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical Chemistry; With 1 vessel the agitator is missing; 1 tank with insulation; 2 claws made of V2A (contact surface the other way around; flanges partly made of Fe (see photos) ; some
Övrig information2: residues of previous content; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1300

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.330 mm
Invändig diameter: 990 mm

Omrörare
Kraft (kW): 1,10
Varvtal: 571

Tjocklek på tank
Botten: 3 mm
Cylinder: 5 mm
Topp: 4,10 mm

Mer
Isolerad: Nej