1300 liter tank i Syrafast 316



75 000 SEK /st exkl moms

Additional information: Pharmacy; Manhole 350 x 450 mm; Outlet fitting incomplete
Volumetric volume (L): 1.300 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 143 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: DN25 DIN 11851
Cylinder: 4 mm

Bottom: 4 mm
Internal diameter tank: 1.100 mm
Cylinder height: 1.250 mm
Total outer length: 2.400 mm

SKU: 409529

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 143 °C
Mobil tank: Nej
Övrig information: Pharmacy; Manhole 350 x 450 mm; Outlet fitting incomplete
Omrörare: Nej
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1300

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.250 mm
Invändig diameter: 1.100 mm

Tjocklek på tank

Botten: 4 mm
Cylinder: 4 mm

Mer
Isolerad: Nej