

1300 liter tank i Syrafast 316



118 000 SEK /st exkl moms

Additional information: Pharmaceutical Chemistry; Further technical documents available; Manhole cover with large sight glass; Loose flanges of the outlet fitting DN 50 & DN 25 made of Fe; bump at the insulation jacket

Volumetric volume (L): 1.300 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 50 L

Max Overpressure: 13 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Cylinder: 5 mm

Bottom: 4,70 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.160 mm

Cylinder height: 1.380 mm

Total height of tank: 2.450 mm

SKU: 289145

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information2: can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1300

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.380 mm
Invändig diameter: 1.000 mm
Total höjd: 2.450 mm
Ytterdiameter: 1.160 mm

Tjocklek på tank

Botten: 4,70 mm
Cylinder: 5 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja