

1300 liter tank i Syrafast 316



119,000,00 kr /st exkl moms

Additional information: Pharmaceutical Chemistry; Further technical documents available; Manhole cover with large sight glass; Loose flanges of the outlet fitting DN 50 & DN 25 made of Fe; bump at the insulation jacket

Volumetric volume (L): 1.300 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 50 L

Max Overpressure: 13 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: available

Cylinder: 5 mm

Bottom: 4,70 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.160 mm

Cylinder height: 1.380 mm

Total height of tank: 2.450 mm

SKU: 289145

Mer information
