1300 liter tank i Syrafast 316



88 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 2 stainless steel 304 brackets (support surface the other way round; see photos); some flanges made of Fe; further technical documentation available; some connections are flanged to the upper bottom or outlet; if these connections are used, the overall height would increase accordingly; some residues of previous content
Volumetric volume (L): 1.300 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 23 L
Max Overpressure: 16 Bar

Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 304
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN80
Top: 4,10 mm

Cylinder: 5 mm
Bottom: 3 mm
Internal diameter tank: 990 mm
Cylinder height: 1.330 mm
Total height of tank: 2.100 mm

SKU: 450272

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); flanges partly made of Fe; further techn. documents available; In some cases,
Övrig information2: connections are flanged in the top bottom or at the outlet; using these connections would increase the overall height accordingly ; some residues of previous content
Omrörare: Nej
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1300

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.330 mm
Invändig diameter: 990 mm
Total höjd: 2.100 mm

Tjocklek på tank
Botten: 3 mm
Cylinder: 5 mm
Topp: 4,10 mm

Mer
Värmeväxlare: RVS 304
Isolerad: Nej