

## 1300 liter tank i Syrafast 316



**88 000 SEK /st exkl moms**

**Additional information:** Pharmaceutical chemistry; 2 stainless steel 304 brackets (support surface the other way round; see photos); some flanges made of Fe; further technical documentation available; some connections are flanged to the upper bottom or outlet; if these connections are used, the overall height would increase accordingly; some residues of previous content

**Volumetric volume (L):** 1.300 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 23 L

**Max Overpressure:** 16 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** flange DN80

**Top:** 4,10 mm

**Cylinder:** 5 mm

**Bottom:** 3 mm

**Internal diameter tank:** 990 mm

**Cylinder height:** 1.330 mm

**Total height of tank:** 2.100 mm

**SKU:** 450272

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); flanges partly made of Fe; further techn. documents available; In some cases,

Övrig information2: connections are flanged in the top bottom or at the outlet; using these connections would increase the overall height accordingly ; some residues of previous content

Omrörare: Nej

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1300

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.330 mm

Invändig diameter: 990 mm

Total höjd: 2.100 mm

## Tjocklek på tank

Botten: 3 mm

Cylinder: 5 mm

Topp: 4,10 mm

## Mer

Värmeväxlare: RVS 304

Isolerad: Nej