13188 liter tank i Rostfritt 304

251 000 SEK /st exkl moms

Additional information: Thermal plates on the cylinder are likely only in the upper part of the cylinder; 1 stronger dent and 1 additional damage to the insulation jacket; Manhole approx. 350 x 460 mm; vent hood incomplete; welded frame parts on the outside of the cylinder (see photos)
Volumetric volume (L): 13.188 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 25 L
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: available
Agitator: yes
Number of revolutions: 14 / 29
Power: 1.2 / 2.2

Internal diameter tank: 1.660 mm
Outer diameter tank: 1.790 mm
Total height of tank: 6.500 mm

SKU: 704419

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Thermal plates on the cylinder are likely only in the upper part of the cylinder; 1 stronger dent and 1 additional damage to the insulation jacket; Manhole approx. 350 x 460 mm; vent hood
Övrig information2: incomplete; welded frame parts on the outside of the cylinder (see photos); we can’t give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Yes
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 13188

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 1.660 mm
Total höjd: 6.500 mm
Ytterdiameter: 1.790 mm

Omrörare
Kraft (kW): 1.2 / 2.2
Varvtal: 14 / 29

Mer
Isolerad: Ja