

13188 liter tank i Rostfritt 304



251 000 SEK /st exkl moms

Additional information: Thermal plates on the cylinder are likely only in the upper part of the cylinder; 1 stronger dent and 1 additional damage to the insulation jacket; Manhole approx. 350 x 460 mm; vent hood incomplete; welded frame parts on the outside of the cylinder (see photos)

Volumetric volume (L): 13.188 L



Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 25 L
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: available
Agitator: yes
Number of revolutions: 14 / 29
Power: 1.2 / 2.2

Internal diameter tank: 1.660 mm
Outer diameter tank: 1.790 mm
Total height of tank: 6.500 mm

SKU: 704419

Mer information



Beskrivning av produkt

Material: Stainless steel 304

Modell: Vertical

Nyttillverkad/Begagnad: Used

Arbetsstryck i tank: ATM – atmospheric

Konfiguration: insulated

Mobil tank: No, it is not.

Övrig information: Thermal plates on the cylinder are likely only in the upper part of the cylinder; 1 stronger dent and 1 additional damage to the insulation jacket; Manhole approx. 350 x 460 mm; vent hood

Övrig information2: incomplete; welded frame parts on the outside of the cylinder (see photos); we can't give any guarantees about the agitator

Omrörare: Yes

Total urtappning: Yes

Uppvärmning/kylning: No, it is not.

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 13188

Utrustning

Dokument finns: No, it is not.

Fläns för omrörare: No

Märkskylt: Yes

Teknisk ritning finns: No, it is not.

Översikt material

Material: Stainless steel 304

Dimensioner av tank

Invändig diameter: 1.660 mm

Total höjd: 6.500 mm

Ytterdiameter: 1.790 mm



Omrörare

Kraft (kW): 1.2 / 2.2

Varvtal: 14 / 29

Mer

Isolerad: Yes