1330 liter tank i Syrafast 316



44 000 SEK /st exkl moms

Additional information: Manhole diameter 350 mm; 2 stainless steel 316 claws; 1 connection bent in the cylinder; connections upper bottom: 1 x DN 100; 5 x DN 50; 2 x DN 25; some residues of previous content
Volumetric volume (L): 1.330 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: DN25 DIN 11851
Top: 4,90 mm

Cylinder: 4,10 mm
Bottom: 5 mm
Internal diameter tank: 1.090 mm
Cylinder height: 1.380 mm
Total height of tank: 2.250 mm

SKU: 449183

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Manhole diameter 350 mm; 2 support brackets, Aisi 316; 1 connection in the cylinder bent; Connections upper bottom: 1 x DN 100; 5 x DN 50; 2 x DN 25 ; some residues of previous content
Omrörare: Nej
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,50 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1330

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.380 mm
Invändig diameter: 1.090 mm
Total höjd: 2.250 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 4,10 mm
Topp: 4,90 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se