

1330 liter tank i Syrafast 316



47,000,00 kr /st exkl moms

Additional information: Manhole diameter 350 mm; 2 support brackets, Aisi 316; 1 connection in the cylinder bent; Connections upper bottom: 1 x DN 100; 5 x DN 50; 2 x DN 25; some residues of previous content

Volumetric volume (L): 1.330 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN25 DIN 11851

Top: 4,90 mm

Cylinder: 4,10 mm

Bottom: 5 mm

Internal diameter tank: 1.090 mm

Cylinder height: 1.380 mm

Total height of tank: 2.250 mm

SKU: N/A



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Manhole diameter 350 mm; 2 support brackets, Aisi 316; 1 connection in the cylinder bent; Connections upper bottom: 1 x DN 100; 5 x DN 50; 2 x DN 25 ; some residues of previous content

Omrörare: Nej

Övertryck: 2 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,50 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1330

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.380 mm

Invändig diameter: 1.090 mm

Total höjd: 2.250 mm

**Tjocklek på tank**

Botten: 5 mm

Cylinder: 4,10 mm

Topp: 4,90 mm

Mer

Isolerad: Nej