

## 1344 liter tank i Syrafast 316



**214,000,00 kr /st exkl moms**

**Additional information:** Pharmacy; The tank was rebuilt at the end of 2012 (socket welding and shortening of the feet; test certificate from TÜV is available; the drawing provided in the appendix is the original drawing; 1 dent in the insulating jacket

**Volumetric volume (L):** 1.344 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 76 L

**Max Overpressure:** 2 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** DN80 DIN 11851

**Agitator:** yes

**Number of revolutions:** 440 / 940

**Power:** 0.33 / 1.85

**Top:** 6 mm

**Cylinder:** 8 mm

**Bottom:** 6,80 mm

**Internal diameter tank:** 1.180 mm

**Outer diameter tank:** 1.350 mm

**Cylinder height:** 750 mm

**Total height of tank:** 2.400 mm

SKU: 313529

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; The tank was rebuilt at the end of 2012 (socket welding and shortening of the feet; test certificate from TÜV is available; the drawing provided in the appendix is the original drawing; 1

Övrig information2: dent in the insulating jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1344



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 750 mm  
Invändig diameter: 1.180 mm  
Total höjd: 2.400 mm  
Ytterdiameter: 1.350 mm

## Omrörare

Kraft (kW): 0.33 / 1.85  
Varvtal: 440 / 940

## Tjocklek på tank

Botten: 6,80 mm  
Cylinder: 8 mm  
Topp: 6 mm

## Mer

Isolerad: Ja