1344 liter tank i Syrafast 316



213 000 SEK /st exkl moms

Additional information: Vessel was converted at the end of 2012 (nozzle welding and shortening of the feet; TÜV test certificate available; the drawing attached is the original drawing; 1 dent in the insulating jacket
Volumetric volume (L): 1.344 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 76 L
Max Overpressure: 2 Bar

Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: DN80 DIN 11851
Agitator: yes

Number of revolutions: 440 / 940
Power: 0.33 / 1.85
Top: 6 mm
Cylinder: 8 mm
Bottom: 6,80 mm

Internal diameter tank: 1.180 mm
Outer diameter tank: 1.350 mm
Cylinder height: 750 mm
Total height of tank: 2.400 mm

SKU: 433877

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Pharmacy; The tank was rebuilt at the end of 2012 (socket welding and shortening of the feet; test certificate from TÜV is available; the drawing provided in the appendix is the original drawing; 1
Övrig information2: dent in the insulating jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1344

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 750 mm
Invändig diameter: 1.180 mm
Total höjd: 2.400 mm
Ytterdiameter: 1.350 mm

Omrörare
Kraft (kW): 0.33 / 1.85
Varvtal: 440 / 940

Tjocklek på tank
Botten: 6,80 mm
Cylinder: 8 mm
Topp: 6 mm

Mer
Isolerad: Ja