

1344 liter tank i Syrafast 316



211 000 SEK /st exkl moms

Additional information: Pharmacy; Vessel was converted at the end of 2012 (nozzle welding and shortening of the feet; TÜV test certificate available; the drawing attached is the original drawing; 1 dent in the insulating jacket

Volumetric volume (L): 1.344 L

Pressure in tank: vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 76 L

Max Overpressure: 2 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN80 DIN 11851

Agitator: yes

Number of revolutions: 440 / 940

Power: 0.33 / 1.85

Top: 6 mm

Cylinder: 8 mm

Bottom: 6,80 mm

Internal diameter tank: 1.180 mm

Outer diameter tank: 1.350 mm

Cylinder height: 750 mm

Total height of tank: 2.400 mm

SKU: 313529

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; The tank was rebuilt at the end of 2012 (socket welding and shortening of the feet; test certificate from TÜV is available; the drawing provided in the appendix is the original drawing; 1

Övrig information2: dent in the insulating jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1344



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 750 mm
Invändig diameter: 1.180 mm
Total höjd: 2.400 mm
Ytterdiameter: 1.350 mm

Omrörare

Kraft (kW): 0.33 / 1.85
Varvtal: 440 / 940

Tjocklek på tank

Botten: 6,80 mm
Cylinder: 8 mm
Topp: 6 mm

Mer

Isolerad: Ja