1345 liter tank i Syrafast 316



88 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; 2 claws made of stainless steel 304 (contact surface the other way round; see photos); flanges partly made of Fe
Volumetric volume (L): 1.345 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Volume: 24 L
Max Overpressure: 16 Bar
Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: available
Cylinder: 5 mm
Bottom: 4,40 mm
Internal diameter tank: 1.000 mm

Cylinder height: 1.370 mm
Total height of tank: 2.350 mm

SKU: 397613

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); flanges partly made of Fe
Omrörare: Nej
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1345

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.370 mm
Invändig diameter: 1.000 mm
Total höjd: 2.350 mm

Tjocklek på tank
Botten: 4,40 mm
Cylinder: 5 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se