

1345 liter tank i Syrafast 316



88,000,00 kr /st exkl moms

Additional information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); flanges partly made of Fe; further techn. documents available; some residues of previous content

Volumetric volume (L): 1.345 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 24 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN80

Top: 5 mm

Cylinder: 5 mm

Bottom: 4 mm

Internal diameter tank: 1.000 mm

Cylinder height: 1.360 mm

Total height of tank: 2.300 mm

SKU: 273496

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); flanges partly made of Fe; further techn. documents available; some residues of

Övrig information2: previous content

Omrörare: Nej

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1345

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.360 mm
Invändig diameter: 1.000 mm
Total höjd: 2.300 mm

Tjocklek på tank

Botten: 4 mm
Cylinder: 5 mm
Topp: 5 mm

Mer

Isolerad: Nej