

## 1345 liter tank i Syrafast 316



**120,000,00 kr /st exkl moms**

**Additional information:** Pharmaceutical Chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); 1 vessel is equipped with insulation (see photos); flanges partly Fe; some residues of previous content

**Volumetric volume (L):** 1.345 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 24 L

**Max Overpressure:** 16 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** flange DN80

**Agitator:** yes

**Number of revolutions:** 313

**Power:** 1,10

**Cylinder:** 5 mm

**Bottom:** 4,40 mm

**Internal diameter tank:** 1.000 mm

**Cylinder height:** 1.370 mm

**Total height of tank:** 2.900 mm

**SKU:** 273820

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry; 2 support brackets made of Aisi 304 (contact surface the other way around; see photos); 1 vessel is equipped with insulation (see photos); flanges partly Fe; some residues

Övrig information2: of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3.20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1345

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.370 mm

Invändig diameter: 1.000 mm

Total höjd: 2.900 mm

## Omrörare

Kraft (kW): 1,10

Varvtal: 313

## Tjocklek på tank

Botten: 4,40 mm

Cylinder: 5 mm

## Mer

Isolerad: Nej