

1350 liter tank i Syrafast 316



38,000,00 SEK /st exkl moms

Additional information: Manhole diameter 350 mm; 2 support brackets, Aisi 316; central bottom outlet was cut off by the previous operator (see photos); Connections upper bottom: 1 x DN 100; 4 x DN 50; 2 x DN 25; 2 x DN 15; 1 used frame made of Fe could be supplied on request at an additional cost (see photos); some residues of previous content

Volumetric volume (L): 1.350 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 0,30 Bar

Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 135 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Internal diameter tank: 990 mm

Cylinder height: 1.380 mm

Total height of tank: 2.200 mm

SKU: 283624

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 135 °C

Mobil tank: Nej

Övrig information: Manhole diameter 350 mm; 2 support brackets, Aisi 316; central bottom outlet was cut off by the previous operator (see photos); Connections upper bottom: 1 x DN 100; 4 x DN 50; 2 x DN 25; 2 x DN 15;

Övrig information2: 1 used frame made of Fe could be supplied on request at an additional cost (see photos) ; some residues of previous content

Omrörare: Nej

Övertryck: 0,30 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,50 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1350

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.380 mm

Invändig diameter: 990 mm

Total höjd: 2.200 mm

Mer

Isolerad: Nej
