1350 liter tank i Syrafast 316



176 000 SEK /st exkl moms

Additional information: Various technical documents available; vessels were suspended by the previous operator in a ring with load cells, which was embedded in the floor (1 ring each is included in the scope of delivery; see photos)
Volumetric volume (L): 1.350 L
Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 80 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 140 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available

Agitator: yes
Number of revolutions: 412
Power: 0,75
Top: 4,50 mm
Internal diameter tank: 1.000 mm

Outer diameter tank: 1.250 mm
Cylinder height: 1.460 mm
Total height of tank: 2.650 mm

SKU: 478383

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: isolert med varmeveksler
Max. arbetstemperatur: 130 °C
Mobil tank: Nej
Övrig information: Pharmacy; Various technical documents available; the previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery;
Övrig information2: see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1350

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.460 mm
Invändig diameter: 1.000 mm
Total höjd: 2.650 mm
Ytterdiameter: 1.250 mm

Omrörare
Kraft (kW): 0,75
Varvtal: 412

Tjocklek på tank
Topp: 4,50 mm

Mer
Isolerad: Ja