

1350 liter tank i Syrafast 316



176,000,00 kr /st exkl moms

Additional information: Pharmacy; Various technical documents available; the previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery; see photos)

Volumetric volume (L): 1.350 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 80 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 140 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 412

Power: 0,75

Top: 4,50 mm

Internal diameter tank: 1.000 mm

Outer diameter tank: 1.250 mm

Cylinder height: 1.460 mm

Total height of tank: 2.650 mm

SKU: 478383

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: Pharmacy; The previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery; see photos); we can't give any

Övrig information2: guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1350

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.460 mm

Invändig diameter: 1.000 mm

Total höjd: 2.650 mm

Ytterdiameter: 1.250 mm

Omrörare

Kraft (kW): 0,75

Varvtal: 412

Tjocklek på tank

Topp: 4,50 mm

Mer

Isolerad: Ja