

## 1350 liter tank i Syrafast 316



**174 000 SEK /st exkl moms**

**Additional information:** Pharmacy; Various technical documents available; vessels were suspended by the previous operator in a ring with load cells, which was embedded in the floor (1 ring each is included in the scope of delivery; see photos)

**Volumetric volume (L):** 1.350 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 130 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 80 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 140 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 412

**Power:** 0,75

**Top:** 4,50 mm

**Internal diameter tank:** 1.000 mm

**Outer diameter tank:** 1.250 mm

**Cylinder height:** 1.460 mm

**Total height of tank:** 2.650 mm

**SKU:** 478383



## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: Pharmacy; Various technical documents available; the previous operator had the vessels hanging in a ring with load cells that was embedded in the ground (1 ring of each is included in the delivery;

Övrig information2: see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1350

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej



## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.460 mm

Invändig diameter: 1.000 mm

Total höjd: 2.650 mm

Ytterdiameter: 1.250 mm

## Omrörare

Kraft (kW): 0,75

Varvtal: 412

## Tjocklek på tank

Topp: 4,50 mm

## Mer

Isolerad: Ja