1350 liter tank i Syrafast 316



131 000 SEK /st exkl moms

Additional information: Chemistry; Vessel probably formerly hung on three screwed support brackets (but these are no longer available); Outside diameter refers to the outside diameter of the insulating jacket (external dirt protection collar plus approx. 100 mm); 2 plastic nuts of the manhole cover attachment are broken; some residues of previous content; dents at the insulation jacket; scratches inside
Volumetric volume (L): 1.350 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 107 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: DN50 DIN 11851

Agitator: yes
Power: 1,60
Internal diameter tank: 1.170 mm
Outer diameter tank: 1.330 mm
Cylinder height: 850 mm

Total height of tank: 2.400 mm

SKU: 407498

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Chemistry; Vessel probably formerly hung on three screwed support brackets (but these are no longer available); Outside diameter refers to the outside diameter of the insulating jacket (external
Övrig information2:
Omrörare: Ja
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1350

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 850 mm
Invändig diameter: 1.170 mm
Total höjd: 2.400 mm
Ytterdiameter: 1.330 mm

Omrörare
Kraft (kW): 1,60

Mer
Isolerad: Ja