

1350 liter tank i Syrafast 316



129,000,00 SEK /st exkl moms

Additional information: Chemistry; Vessel probably formerly hung on three screwed support brackets (but these are no longer available); Outside diameter refers to the outside diameter of the insulating jacket (external dirt protection collar plus approx. 100 mm); 2 plastic nuts of the manhole cover attachment are broken; some residues of previous content; dents at the insulation jacket; scratches inside

Volumetric volume (L): 1.350 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 107 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Agitator: yes

Power: 1,60

Internal diameter tank: 1.170 mm

Outer diameter tank: 1.330 mm

Cylinder height: 850 mm

Total height of tank: 2.400 mm

SKU: 283450

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Vessel probably formerly hung on three screwed support brackets (but these are no longer available); Outside diameter refers to the outside diameter of the insulating jacket (external

Övrig information2:

Omrörare: Ja

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1350

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 850 mm

Invändig diameter: 1.170 mm

Total höjd: 2.400 mm

Ytterdiameter: 1.330 mm

Omrörare

Kraft (kW): 1,60

Mer

Isolerad: Ja