13500 liter tank i Rostfritt 304



118 000 SEK /st exkl moms

Additional information: Small dents in the inner cylinder; insulation of the lower base no longer complete; some residues of previous content; bump at the insulation jacket; Functionality of the double jacket not checked
Volumetric volume (L): 13.500 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside
Outlet of tank: 70
Agitator: yes

Number of revolutions: 690 / 1390
Internal diameter tank: 2.190 mm
Outer diameter tank: 2.350 mm
Cylinder height: 3.700 mm
Total height of tank: 5.650 mm

SKU: 401906

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Small dents in inner cylinder; insulation of the lower bottom no longer complete; some residues of previous content;bump at the insulation jacket;Functionality of the double jacket not checked; we
Övrig information2: can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 13500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 3.700 mm
Invändig diameter: 2.190 mm
Total höjd: 5.650 mm
Ytterdiameter: 2.350 mm

Omrörare
Varvtal: 690 / 1390

Mer
Värmeväxlare: RVS 304
Isolerad: Ja