13600 liter tank i Syrafast 316



162 000 SEK /st exkl moms

Additional information: Extensive documentation available; tank by now already dismantled and warehoused horizontally; two tanks with damaged insulation jacket, which likely needs replacement; legs of the storage tank are shorter than the lower bottom.
Volumetric volume (L): 13.600 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 50 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: headside
Outlet of tank: available
Top: 5 mm
Cylinder: 4 mm
Bottom: 5 mm

Internal diameter tank: 1.792 mm
Outer diameter tank: 1.800 mm
Total height of tank: 5.930 mm

SKU: 477463

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Max. arbetstemperatur: 50 °C
Mobil tank: Nej
Övrig information: Extensive documentation available; tank by now already dismantled and warehoused horizontally; two tanks with damaged insulation jacket, which likely needs replacement; legs of the storage tank are
Övrig information2: shorter than the lower bottom.
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 13600

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.792 mm
Total höjd: 5.930 mm
Ytterdiameter: 1.800 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 4 mm
Topp: 5 mm

Mer
Isolerad: Nej