13600 liter tank i Syrafast 316

142 000 SEK /st exkl moms

Additional information: waterfilter in the beverage industry; welded filter plate inside (see pictures); output 60 cbm/h; nozzles of the filter plate made of plastic; some residues of previous content
Volumetric volume (L): 13.600 L
Pressure in tank: pressure
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Max Overpressure: 6 Bar
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: flange DN100
Cylinder: 7,60 mm
Bottom: 11,50 mm

Internal diameter tank: 2.280 mm
Cylinder height: 2.500 mm
Total height of tank: 4.450 mm

SKU: 389618

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: waterfilter in the beverage industry; welded filter plate inside (see pictures); output 60 cbm/h; nozzles of the filter plate made of plastic; some residues of previous content
Omrörare: Nej
Övertryck: 6 Bar
Total urtappning: Ja
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 13600

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 2.280 mm
Total höjd: 4.450 mm

Tjocklek på tank
Botten: 11,50 mm
Cylinder: 7,60 mm

Mer
Isolerad: Nej