

## 1370 liter tank i Syrafast 316



**164 000 SEK /st exkl moms**

**Additional information:** Pharmacy; Further technical documents available

**Volumetric volume (L):** 1.370 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 32 L

**Max Overpressure:** 2,50 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** DN25 DIN 11851

**Agitator:** yes

**Number of revolutions:** 247

**Power:** 1,50

**Cylinder:** 4 mm

**Bottom:** 5 mm

**Internal diameter tank:** 1.000 mm

**Outer diameter tank:** 1.136 mm

**Cylinder height:** 1.500 mm

**Total height of tank:** 3.350 mm

**SKU:** 293893

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Pharmacy; Further technical documents available; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1370

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

## **Dimensioner av tank**

Cylinderhöjd: 1.500 mm  
Invändig diameter: 1.000 mm  
Total höjd: 3.350 mm  
Ytterdiameter: 1.136 mm

## **Omrörare**

Kraft (kW): 1,50  
Varvtal: 247

## **Tjocklek på tank**

Botten: 5 mm  
Cylinder: 4 mm

## **Mer**

Isolerad: Ja