

13800 liter tank i Syrafast 316



153 000 SEK /st exkl moms

Additional information: chemistry; tank with adhesions inside; diameter manhole appr. 600 mm; manhole cover plated

Volumetric volume (L): 13.800 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: flange DN150

Top: 16 mm

Cylinder: 9 mm

Bottom: 11,60 mm

Internal diameter tank: 2.190 mm

Cylinder height: 2.990 mm

Total height of tank: 4.900 mm

SKU: 272752

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: chemistry; tank with adhesions inside; diameter manhole appr. 600 mm; manhole cover plated

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 13800

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.990 mm

Invändig diameter: 2.190 mm

Total höjd: 4.900 mm

Tjocklek på tank

Botten: 11,60 mm

Cylinder: 9 mm

Topp: 16 mm

Mer

Isolerad: Nej