

14000 liter tank i Rostfritt 304



111,000,00 kr /st exkl moms

Additional information: Double jacket, Aisi 304 for heating/cooling around the lower cylinder area and the lower bottom; lower inner bottom with dents; Manhole approx. 320 x 420 mm (1 connection in the manhole cover torn; see photos); some residues of previous content

Volumetric volume (L): 14.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 100
Agitator: yes

Number of revolutions: 9,50
Power: 11
Cylinder: 4,10 mm
Bottom: 4,10 mm
Internal diameter tank: 2.400 mm

Outer diameter tank: 2.480 mm
Cylinder height: 2.980 mm
Total height of tank: 5.350 mm

SKU: 275809

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Double jacket, Aisi 304 for heating/cooling around the lower cylinder area and the lower bottom; lower inner bottom with dents; Manhole approx. 320 x 420 mm (1 connection in the manhole cover torn;

Övrig information2: see photos) ; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 14000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.980 mm
Invändig diameter: 2.400 mm
Total höjd: 5.350 mm
Ytterdiameter: 2.480 mm

Omrörare

Kraft (kW): 11
Varvtal: 9,50

Tjocklek på tank

Botten: 4,10 mm
Cylinder: 4,10 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej