14000 liter tank i Rostfritt 304



99 000 SEK /st exkl moms

Additional information: recycling industry; insulation jacket with dents and cut-outs; 1 opening appr. 310 mm in the upper bottom; feet plates bent; 1 tank with dents in the cylinder; the other tank with stronger adhesions inside and a hole in the outlet pipe; some residues of previous content
Volumetric volume (L): 14.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: 85
Agitator: yes
Number of revolutions: 20
Power: 2,20
Internal diameter tank: 1.990 mm

Outer diameter tank: 2.200 mm
Cylinder height: 4.000 mm
Total height of tank: 6.200 mm

SKU: 394001

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: recycling industry; insulation jacket with dents and cut-outs; 1 opening appr. 310 mm in the upper bottom; feet plates bent; 1 tank with dents in the cylinder; the other tank with stronger adhesions
Övrig information2: inside and a hole in the outlet pipe; some residues of previous content; we can’t give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 14000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 4.000 mm
Invändig diameter: 1.990 mm
Total höjd: 6.200 mm
Ytterdiameter: 2.200 mm

Omrörare
Kraft (kW): 2,20
Varvtal: 20

Mer
Isolerad: Ja