

1410 liter tank i Syrafast 316



190 000 SEK /st exkl moms

Additional information: Cosmetics; 4 stainless steel claws; total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; 1 dirt protection collar on the outside above the claws (diameter approx. 1,740 mm)

Volumetric volume (L): 1.410 L

Pressure in tank: vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 93 L

Max Overpressure: 4 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 65

Agitator: yes

Number of revolutions: 960

Power: 3

Top: 6,10 mm

Cylinder: 8,40 mm

Bottom: 6,90 mm

Internal diameter tank: 1.300 mm

Outer diameter tank: 1.450 mm

Cylinder height: 700 mm

Total height of tank: 2.250 mm

SKU: 434294

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Cosmetics; 4 support brackets, stainless steel; Total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; 1 dirt protection collar on the outside over

Övrig information2: the support brackets (diameter approx. 1,740 mm); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1410



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 700 mm
Invändig diameter: 1.300 mm
Total höjd: 2.250 mm
Ytterdiameter: 1.450 mm

Omrörare

Kraft (kW): 3
Varvtal: 960

Tjocklek på tank

Botten: 6,90 mm
Cylinder: 8,40 mm
Topp: 6,10 mm

Mer

Isolerad: Ja