

## 1410 liter tank i Syrafast 316



**192,000,00 kr /st exkl moms**

**Additional information:** Cosmetics; 4 support brackets, stainless steel; Total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; 1 dirt protection collar on the outside over the support brackets (diameter approx. 1,740 mm)

**Volumetric volume (L):** 1.410 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 93 L

**Max Overpressure:** 4 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 65

**Agitator:** yes

**Number of revolutions:** 960

**Power:** 3

**Top:** 6,10 mm

**Cylinder:** 8,40 mm

**Bottom:** 6,90 mm

**Internal diameter tank:** 1.300 mm

**Outer diameter tank:** 1.450 mm

**Cylinder height:** 700 mm

**Total height of tank:** 2.250 mm

SKU: 434294

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Cosmetics; 4 support brackets, stainless steel; Total height is estimated; 1 heating connection cut off; slight metallic discoloration inside the tank; 1 dirt protection collar on the outside over

Övrig information2: the support brackets (diameter approx. 1,740 mm); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1410



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 700 mm  
Invändig diameter: 1.300 mm  
Total höjd: 2.250 mm  
Ytterdiameter: 1.450 mm

## Omrörare

Kraft (kW): 3  
Varvtal: 960

## Tjocklek på tank

Botten: 6,90 mm  
Cylinder: 8,40 mm  
Topp: 6,10 mm

## Mer

Isolerad: Ja