1410 liter tank i Syrafast 316



191 000 SEK /st exkl moms

Additional information: 4 stainless steel claws; total height is estimated; slight metallic discoloration inside the tank
Volumetric volume (L): 1.410 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 93 L
Max Overpressure: 4 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: 65
Agitator: yes
Number of revolutions: 960
Power: 3
Top: 6,10 mm

Cylinder: 8,40 mm
Bottom: 6,90 mm
Internal diameter tank: 1.300 mm
Outer diameter tank: 1.450 mm
Cylinder height: 700 mm

Total height of tank: 2.400 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

SKU: 434231

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Cosmetics; 4 support brackets, stainless steel; Total height is estimated; slight metallic discoloration inside the tank; we can't give any guarantees about the heating/cooling jacket; we can't give
Övrig information2: any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 1410

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 700 mm
Invändig diameter: 1.300 mm
Total höjd: 2.400 mm
Ytterdiameter: 1.450 mm

Omrörare
Kraft (kW): 3
Varvtal: 960

Tjocklek på tank
Botten: 6,90 mm
Cylinder: 8,40 mm
Topp: 6,10 mm

Mer
Värmeväxlare: RVS 304
Isolerad: Ja