14300 liter tank i Rostfritt 304



89 000 SEK /st exkl moms

Additional information: coatings industry; 2 feet shorter than the others; feet with a welded metall part or a steel girder under the bottom plate (see pictures); for installation the feet needs to be reworked; diameter manhole 600 mm; some residues of previous content; manhole cover plated
Volumetric volume (L): 14.300 L
Pressure in tank: pressure

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 0,50 Bar
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Max Overpressure: 0,50 Bar
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: cylinder
Outlet of tank: 88
Cylinder: 3 mm
Bottom: 4 mm

Internal diameter tank: 2.480 mm
Cylinder height: 2.250 mm
Total height of tank: 3.750 mm

SKU: 394142

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: coatings industry; 2 feet shorter than the others; feet with a welded metall part or a steel girder under the bottom plate (see pictures); for installation the feet needs to be reworked; diameter
Övrig information2: manhole 600 mm; some residues of previous content;manhole cover plated
Omrörare: Nej
Övertryck: 0,50 Bar
Total urtappning: Ja
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 14300

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.250 mm
Invändig diameter: 2.480 mm
Total höjd: 3.750 mm

Tjocklek på tank
Botten: 4 mm
Cylinder: 3 mm

Mer
Isolerad: Nej