

150 liter tank i Syrafast 316



99,000,00 kr /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SLA

Additional information: delivered with food certificate; *article price without agitator*; choice of 2 different types of agitators; see options; (The article can also be purchased without options); $Ra < 0.8 \mu m$

Volumetric volume (L): 150 L

Max. density P (kg/m³): 1.300

Ra inner weld: 0,80

Finish stainless steel: 2b



Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: half hinging lid °
Shape of tank: cylindrical
Bottom type: conical 10 °
Total discharge: yes
Fixation points: 3 non adjustable feet

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: yes
Registration plate on the tank: no

Flange for agitator: no
CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851
Agitator: no, optional

Top: 3 mm
Cylinder: 3 mm
Bottom: 3 mm
Distance from outlet to ground: 250 mm
Outer diameter tank: 605 mm

Cylinder height: 500 mm
Total height of tank: 1.400 mm
Empty weight tank: 70

SKU: 10784

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1300

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 150



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 500 mm
Mått utlopp till marken: 250 mm
Total höjd: 1.400 mm
Ytterdiameter: 605 mm

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Mer

Isolerad: Nej
Vikt: 70