

150 liter tank i Syrafast 316



116,000,00 kr /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SCA

Additional information: delivered with food certificate; *article price without agitator*; choice of 2 different types of agitators; see options; (The article can also be purchased without options); $Ra < 0.8 \mu m$

Volumetric volume (L): 150 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: yes

Top type: half hinging lid

With blocking system: yes

Shape of tank: cylindrical

Bottom type: conical 20 °

Total discharge: yes

Fixation points: 4 casters

Spray ball: RVS 316L

Gasket manway(s): EPDM

Valve: RVS 316L

Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: yes

Flange type: Tri-Clamp DN150

CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm

Outlet type: DIN32676 clamp

Total outlet valve: no, optional

Agitator: no, optional

Top: 5 mm

Cylinder: 2,50 mm

Bottom: 2 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 605 mm

Cylinder height: 500 mm

Total height of tank: 1.500 mm

Empty weight tank: 62

SKU: 10898

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Ja

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 20 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 150

Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN32676 clamp

Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 500 mm
Mått utlopp till marken: 250 mm
Total höjd: 1.500 mm
Ytterdiameter: 605 mm

Tjocklek på tank

Botten: 2 mm
Cylinder: 2,50 mm
Topp: 5 mm

Mer

Isolerad: Nej
Vikt: 62