

## 150 liter tank i Syrafast 316



**81 000 SEK /st exkl moms**

**Additional information:** Mobile stainless steel 316 frame with 4 plastic wheels; handle hole diameter approx. 200 mm; includes complete documentation from a GMP-certified pharmaceutical manufacturing facility

**Volumetric volume (L):** 150 L



**Pressure in tank:** vacuum

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 140 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** 29

**Agitator:** yes

**Number of revolutions:** 52 - 525

**Power:** 0,18

**Top:** 25 mm

**Cylinder:** 3,50 mm

**Bottom:** 4,10 mm

**Internal diameter tank:** 540 mm

**Cylinder height:** 570 mm

**Total height of tank:** 1.450 mm

**SKU:** 706789



## Mer information

### Beskrivning av produkt

Material: Syrefast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Brukt

Arbetsstryck i tank: vakuum

Konfiguration: enkelthudet

Max. arbetstemperatur: 140 °C

Mobil tank: Nei, det er det ikke.

Övrig information: Mobile stainless steel 316 frame with 4 plastic wheels; handle hole diameter approx. 200 mm; includes complete documentation from a GMP-certified pharmaceutical manufacturing facility; we can't give

Övrig information2: noen garantier om omrøreren

Omrørare: Ja

Total urtappning: Ja

Undertryck (vakuum): 1 bar

Uppvärmning/kylning: Nei, det er det ikke.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 150

### Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrørare: Nei

Märkskylt: Ja

Teknisk ritning finns: Nei, det er det ikke.

### Översikt material

Material: Syrefast 316

### Dimensioner av tank

Cylinderhöjd: 570 mm

Invändig diameter: 540 mm (18 tommer)

Total höjd: 1 450 mm

**Omrörare**

Kraft (kW): 0,18  
Varvtal: 52 – 525

**Tjocklek på tank**

Botten: 4,10 mm  
Cylinder: 3,50 mm  
Topp: 25 mm

**Mer**

Isolerad: Nei