

150 liter tank i Syrafast 316



295,000,00 kr /st exkl moms

Additional information: Vessel was only used for validation and never went into service; technical documentation was ordered from the manufacturer but has not yet arrived; plastic casters on the feet were unscrewed for shipping but are included loose (see photos)

Volumetric volume (L): 150 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 11 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 95 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 25

Agitator: yes

Number of revolutions: 125 - 800

Power: 0,09

Top: 6 mm

Cylinder: 5 mm

Bottom: 4 mm

Internal diameter tank: 490 mm

Outer diameter tank: 550 mm

Cylinder height: 630 mm

Total height of tank: 1.750 mm

SKU: 483806

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Vessel was only used for validation and never went into service; technical documentation was ordered from the manufacturer but has not yet arrived; plastic casters on the feet were unscrewed for

Övrig information2: shipping but are included loose (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 150

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 630 mm
Invändig diameter: 490 mm
Total höjd: 1.750 mm
Ytterdiameter: 550 mm

Omrörare

Kraft (kW): 0,09
Varvtal: 125 – 800

Tjocklek på tank

Botten: 4 mm
Cylinder: 5 mm
Topp: 6 mm

Mer

Isolerad: Ja