

## 150 liter tank i Syrafast 316



**289 000 SEK /st exkl moms**

**Additional information:** Vessel was only tested for validation purposes; technical documentation was ordered from the manufacturer, but has not yet arrived; plastic rollers for the feet were unscrewed for shipping, but are enclosed loose (see photos)

**Volumetric volume (L):** 150 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 95 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 11 L

**Max Overpressure:** 6 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 95 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** 25

**Agitator:** yes

**Number of revolutions:** 125 - 800

**Power:** 0,09

**Top:** 6 mm

**Cylinder:** 5 mm

**Bottom:** 4 mm

**Internal diameter tank:** 490 mm

**Outer diameter tank:** 550 mm

**Cylinder height:** 630 mm

**Total height of tank:** 1.750 mm

SKU: 483806

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Vessel was only used for validation and never went into service; technical documentation was ordered from the manufacturer but has not yet arrived; plastic casters on the feet were unscrewed for

Övrig information2: shipping but are included loose (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 150



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Ja  
Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 630 mm  
Invändig diameter: 490 mm  
Total höjd: 1.750 mm  
Ytterdiameter: 550 mm

## Omrörare

Kraft (kW): 0,09  
Varvtal: 125 – 800

## Tjocklek på tank

Botten: 4 mm  
Cylinder: 5 mm  
Topp: 6 mm

## Mer

Isolerad: Ja