

# 150 liter tank i Syrafast 316



## 135,000 SEK /st exkl moms

**Volumetric volume (L):** 150 L

**Pressure in tank:** pressure

**Max. pressure (Bar):** 1,50 Bar

**Max. temperature (°C):** 70 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Max Overpressure:** 1,50 Bar

**Max. working temperature:** 80 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 1.500

**Internal diameter tank:** 610 mm

**Outer diameter tank:** 770 mm

**Total height of tank:** 1.650 mm

**SKU:** 490767

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 70 °C

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 1,50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 150

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## **Dimensioner av tank**

Invändig diameter: 610 mm

Total höjd: 1.650 mm

Ytterdiameter: 770 mm

## **Omrörare**

Varvtal: 1.500

## **Mer**

Isolerad: Ja