

150 liter tank i Syrafast 316



119 000 SEK /st exkl moms

Additional information: Mobile stainless steel 316 frame with 4 plastic wheels; handle hole diameter approx. 200 mm; includes complete documentation from a GMP-certified pharmaceutical manufacturing facility

Volumetric volume (L): 150 L



Pressure in tank: vacuum

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 16 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 140 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 29

Agitator: yes

Number of revolutions: 52 - 525

Power: 0,18

Top: 25 mm

Cylinder: 5,10 mm

Bottom: 4,10 mm

Internal diameter tank: 538 mm

Outer diameter tank: 700 mm

Cylinder height: 575 mm

Total height of tank: 1.400 mm

SKU: 707005



Mer information

Beskrivning av produkt

Material: Acid-resistant 316

Modell: Vertical

Nyttillverkad/Begagnad: Used

Arbetsstryck i tank: vacuum

Konfiguration: insulated

Max. arbetstemperatur: 140 °C

Mobil tank: No, it is not.

Övrig information: Mobile stainless steel 316 frame with 4 plastic wheels; handle hole diameter approx. 200 mm; includes complete documentation from a GMP-certified pharmaceutical manufacturing facility; we can't give

Övrig information2: any guarantees about the agitator

Omrörare: Yes

Total urtappning: Yes

Undertryck (vakuum): 1 bar

Uppvärmning/kylning: No, it is not.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 150

Utrustning

Dokument finns: No, it is not.

Fläns för omrörare: No

Märkskylt: Yes

Teknisk ritning finns: No, it is not.

Översikt material

Material: Acid-resistant 316



Dimensioner av tank

Cylinderhöjd: 575 mm
Invändig diameter: 538 mm
Total höjd: 1.400 mm
Ytterdiameter: 700 mm

Omrörare

Kraft (kW): 0,18
Varvtal: 52 – 525

Tjocklek på tank

Botten: 4,10 mm
Cylinder: 5,10 mm
Topp: 25 mm

Mer

Isolerad: Yes