

1500 liter tank i Rostfritt 304



107,000,00 kr /st exkl moms

Article type: second-hand pressure tank

Additional information: The lid for the smaller connection on the top is missing, the cap for the electromotor is missing, the nuts for the manway are missing; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 1.500 L

Ra inner weld: 0,80

Pressure in tank: pressure

Design pressure (Bar): 5,25 Bar

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): -1 Bar
Max. temperature (°C): 135 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Top type: dished
Shape of tank: cylindrical
Bottom type: dished
Total discharge: yes
Fixation points: 3 non adjustable feet

Water pressure HE: 5 Bar
Hydraulic test pressure: 6,89 Bar
Working temperature HE cylinder: 135 °C
Manway(s): RVS 304
Gasket manway(s): unknown

Valve: RVS 304
Gasket shut-off valve (mat): unknown
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Total outlet valve: yes
Agitator: yes
Agitator type: tripod
Position engine: in the bottom

Outer diameter tank: 1.500 mm

Total height of tank: 2.000 mm

Empty weight tank: 750

SKU: 20070

Mer information
