

1500 liter tank i Rostfritt 304



97,000,00 kr /st exkl moms

Additional information: Food industry; 2 loading trolleys, Aisi 304 are included in the scope of delivery; 1 tank approx. 200 mm shorter in total length due to a cut rod; some residues of previous content

Volumetric volume (L): 1.500 L

Pressure in tank: pressure



Max. pressure (Bar): 3 Bar

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 180 L

Max Overpressure: 3 Bar

Max. working temperature: 130 °C

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN50

Cylinder: 6 mm

Bottom: 3,40 mm

Internal diameter tank: 958 mm

Outer diameter tank: 1.150 mm

Total height of tank: 1.900 mm

Total outer length: 2.950 mm

SKU: 303048

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 120 °C

Mobil tank: Nej

Övrig information: Food industry; 2 loading trolleys, Aisi 304 are included in the scope of delivery; 1 tank approx. 200 mm shorter in total length due to a cut rod; some residues of previous content; we can't give

Övrig information2: any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 1500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 958 mm

Total höjd: 1.900 mm

Ytterdiameter: 1.150 mm

Tjocklek på tank

Botten: 3,40 mm

Cylinder: 6 mm

Mer

Isolerad: Ja