1500 liter tank i Rostfritt 304



121 000 SEK /st exkl moms

Article type: second-hand pressure tank
Additional information: Full vacuum -1 bar; we can't give any guarantees about the heating/cooling jacket
Volumetric volume (L): 1.500 L
Pressure in tank: pressure
Max. pressure (Bar): 0,49 Bar

Min. pressure (Bar): -1 Bar
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mobile tank: no
Top type: dished
Shape of tank: cylindrical
Bottom type: dished

Total discharge: yes
Fixation points: 3 adjustable feet
Heat exchanger: RVS 304
Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Height manhole 1 (mm): 320 mm
Tank outlet: inside Ø 32 mm
Total outlet valve: no
Agitator: no
Insulation body: yes

Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 50
Internal diameter tank: 900 mm
Distance from outlet to ground: 600 mm

Outer diameter tank: 1.000 mm
Cylinder height: 2.060 mm
Total height of tank: 3.100 mm

SKU: 461541

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Full vacuum -1 bar; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 0,49 Bar
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: dished
Undertryck (vakuum): -1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 1500

Utrustning
Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 32 mm
Teknisk ritning finns: Nej
Utloppsventil: Nej

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank
Cylinderhöjd: 2.060 mm
Invändig diameter: 900 mm
Mått utlopp till marken: 600 mm
Total höjd: 3.100 mm
Ytterdiameter: 1.000 mm

Tjocklek på ytterbeklädnad och isolering
Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer
Värmeväxlare: RVS 304
Isoleringstjocklek OW: 50
Isolerad: Ja