

1500 liter tank i Syrafast 316



101 000 SEK /st exkl moms

Additional information: Manhole 400 x 500 mm; total height as specified includes railing; a DN 80 fitting with a gate valve is flanged to the outlet

Volumetric volume (L): 1.500 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 60 °C



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: DN80 DIN 11851

Agitator: yes

Number of revolutions: 20 / 40

Power: 0.66 / 1.33

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.300 mm

Outer diameter tank: 1.400 mm

Cylinder height: 1.500 mm

Total height of tank: 4.550 mm

SKU: 703301



Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: insulated

Max. arbetstemperatur: 60 °C

Mobil tank: Nej

Övrig information: Food; Manhole diameter: approx. 530 x 430 mm; dimensions as shown in the drawing

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 1500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 1.300 mm

Total höjd: 3.190 mm

Ytterdiameter: 1.400 mm



Omrörare

Kraft (kW): 0.66 / 1.33

Varvtal: 20 / 40

Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Mer

Isolerad: Ja