

1500 liter tank i Syrafast 316



242,000,00 kr /st exkl moms

Additional information: Manhole diameter approx. 490 mm; several stainless steel sheets have been welded into the insulating jacket by the previous operator (see photos)

Volumetric volume (L): 1.500 L

Pressure in tank: pressure and vacuum



Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 110 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 80

Agitator: yes

Number of revolutions: 173

Power: 5,50

Internal diameter tank: 1.480 mm

Outer diameter tank: 1.650 mm

Total height of tank: 3.400 mm

SKU: 287540

Mer information
