

1500 liter tank i Syrafast 316



243 000 SEK /st exkl moms

Additional information: Manhole diameter approx. 490 mm; several stainless steel sheets have been welded into the insulating jacket by the previous operator (see photos)

Volumetric volume (L): 1.500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 110 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 80

Agitator: yes

Number of revolutions: 173

Power: 5,50

Internal diameter tank: 1.480 mm

Outer diameter tank: 1.650 mm

Total height of tank: 3.400 mm

SKU: 287540

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Manhole diameter approx. 490 mm; several stainless steel sheets have been welded into the insulating jacket by the previous operator (see photos); we can't give any guarantees about the

Övrig information2: heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 1500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 1.480 mm

Total höjd: 3.400 mm

Ytterdiameter: 1.650 mm

Omrörare

Kraft (kW): 5,50

Varvtal: 173

Mer

Värmeväxlare: RVS 304

Isolerad: Ja