

15000 liter tank i Rostfritt 304



212,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 adjustable feet

Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 500 mm
Tank outlet: inside Ø 80 mm
Total outlet valve: no

Agitator: yes
Agitator type: tripod
Position engine: at the top
Number of revolutions: 18 / 36
Power: 2,20

Voltage: three-phase
Insulation body: yes
Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 60

Internal diameter tank: 2.650 mm
Distance from outlet to ground: 600 mm
Outer diameter tank: 2.800 mm
Cylinder height: 2.750 mm

Total height of tank: 5.400 mm

Empty weight tank: 1.300

SKU: 20835

Mer information
