

15000 liter tank i Rostfritt 304



95,000,00 kr /st exkl moms

Article type: second-hand storage tank

Additional information: There is still some leftover from the previous product; the previous product was beer

Volumetric volume (L): 15.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes



Insulation: no
Mobile tank: no

Top type: dished
Shape of tank: cylindrical
Bottom type: dished
Bottom outlet: yes
Total discharge: no

Fixation points: 3 non adjustable feet
Type of HE on the cylinder: dimple-jacket
Position HE: top side of the cilinder
Height per section: 900 mm
Water pressure HE: 2 Bar

Heat exchanger: RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Agitator: no, optional
Distance from outlet to ground: 180 mm

Outer diameter tank: 2.500 mm
Cylinder height: 3.000 mm
Total height of tank: 4.400 mm
Empty weight tank: 1.200

SKU: 299468

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: There is still some leftover from the previous product; the previous product was beer

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Nej

Typ av botten: dished

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 15000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304



Dimensioner av tank

Cylinderhöjd: 3.000 mm
Mått utlopp till marken: 180 mm
Total höjd: 4.400 mm
Ytterdiameter: 2.500 mm

Värmeväxlare

Position värmeväxlare: top side of the cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Vattentryck värmeväxlare: 2 Bar

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 1.200